


Unsplit long arm



Split long arm

Range: 3800 Kg - 5600 Kg

- Rotating paper roll clamp for safe and effective vertical and horizontal roll handling.
- Slim and smooth arm and frame design, optimal visibility and advanced hydraulic operation.
- Pivoting arm movement. Short and long arms. Non-split long arm for single roll handling. Split arm for 1 - 2 roll handling.
- 180-degree rotation. Hydraulic cushioning in the vertical end positions.
- All hydraulic functions protected with built-in pressure relief valves and check valves. All service and maintenance points easily available.

Model	Capacity	Load Centre	Roll Range	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	<i>Q</i> kg	<i>BP</i> mm	<i>A</i> mm	<i>D</i> mm	<i>W</i> Kg	<i>HCG</i> mm	<i>VCG</i> mm	<i>LL</i> mm	<i>M x N</i> mm	<i>O</i> mm	<i>H</i> mm	<i>ISO</i> 2328
Single roll clamps - Unsplit long arm												
AR-53RH-13	5600	650	400-1300	1240	1415	290	520	240	280x500	200	100	4 A
AR-53RH-14	5500	700	430-1400	1240	1420	300	520	240	280x500	200	100	4 A
AR-53RH-15	5400	760	470-1520	1240	1450	315	520	240	280x500	200	100	4 A
AR-53RH-16	5300	800	500-1600	1240	1470	325	520	240	280x500	200	100	4 A
AR-53RH-17	5000	850	600-1700	1240	1485	340	520	240	280x500	200	100	4 A
AR-53RH-18	4600	915	560-1830	1240	1515	355	520	240	280x500	200	100	4 A
AR-53RH-19	4300	950	550-1900	1240	1530	365	520	240	280x500	200	100	4 A
AR-53RH-20	4000	1000	550-2000	1240	1550	380	520	240	280x500	200	100	4 A
AR-53RH-21	3800	1050	600-2100	1240	1590	400	520	240	280x500	200	100	4 A
1 - 2 roll clamps - Split long arm												
AR-53RJ-13	5600	650	400-1300	1240	1405	285	520	240	280x500	200	100	4 A
AR-53RJ-14	5500	700	430-1400	1240	1410	295	520	240	280x500	200	100	4 A
AR-53RJ-15	5400	760	470-1520	1240	1440	310	520	240	280x500	200	100	4 A
AR-53RJ-16	5300	800	500-1600	1240	1460	320	520	240	280x500	200	100	4 A
AR-53RJ-17	5000	850	600-1700	1240	1475	330	520	240	280x500	200	100	4 A
AR-53RJ-18	4600	915	560-1830	1240	1505	345	520	240	280x500	200	100	4 A
AR-53RJ-19	4300	950	550-1900	1240	1525	355	520	240	280x500	200	100	4 A
AR-53RJ-20	4000	1000	550-2000	1240	1545	370	520	240	280x500	200	100	4 A
AR-53RJ-21	3800	1050	600-2100	1240	1585	390	520	240	280x500	200	100	4 A

Notes:

- Two hydraulic functions required.
- Standard contact pads: cast pad with high-friction surface.
- Minimum 5-degree forward tilt on lift mast is required for horizontal handling.
- For 0-degree tilt, special arms are available. Consult Bolzoni.

Options:

- Special roll ranges.
- Contact pad options:
 - steel-sprayed
 - rubber faced
 - polyurethane faced
 - full length contact pads.

